

SETTING NEW
STANDARDS



H Y P E R
G R I N D E R

H R C
650



MADE IN ITALY

HRC 650



PROFESSIONAL TECHNOLOGICAL GRINDER

The DCT system allows you to choose to smooth use only using the rotation of the tools (DCT ON mode), or with the classic complete rotation of the planetary (DCT OFF mode).

MAIN CHARACTERISTICS:



- Single-shell chassis, robust and compact for less space.
- 180° overturning system for extra weight. The displaced weights increase the grinding pressure. The weights moved back facilitate the tilting operation for tool changes. (Optional)
- 46 litre water tank.
- Powerful front and rear LED spotlights (optional).
- Total transmission with heat treated gears for maximum reliability and durability.
- Noise reduction levitating planetarium.
- 2 Year Warranty: The GUARANTEE for machines equipped with "hour counter" is up to 2 years or 600 hours of work.

TECHNICAL DATA


Model	Motor	Drive Inverter	Volt	Hertz	Amp	Tool Speed	Work Diameter	Tool Size	Water Tank	Size LxAxP cm	Weight
HRC 650 VS	10 HP	7,5 kW	380/480	50/60	16	600-1300 rpm	650mm	3x240mm	46 lt	120x125x67	340 Kg

Professional grinder with exclusive **double rotation system** OCTO “Dual Cut Tech”.


Anti-shock system for maximum reliability.



FULL METAL GEAR BOX. PLANETARY HEAD that is 100% tempered metal and geared driven not belt.



Drive lever system. OCT.



POWERFUL FRONT AND REAR LED (OPTIONAL)

ESTIMATED PRODUCTION

Concrete Polishing 7 step	12-17 m ² /h
Concrete Grinding 1 step	50-90 m ² /h
Terrazzo Polishing 5 step	11-17 m ² /h
Resin Removal 1 step	45-85 m ² /h
Paint Removal 1 step	45-85 m ² /h
Marble Polishing 5 step	8-13 m ² /h
Granite Polishing 7 step	5-8 m ² /h

Data may vary depending on surface conditions, tools used, operator convenience, equipment, etc.



Volume
1,31 m³

Size
120x80x136 cm

Weight
403 Kg

DOUBLE CUT TECH


The new range of HRC grinders introduces the exclusive DCT transmission. Thanks to this innovative function, it is possible to lock the rotation of the main plate and allow only the rotation of the tools simply by pressing a lever on the planetary (DCT ON). With the DCT in the ON position you gain higher speeds of the satellites for a more aggressive and effective grinding. The DCT ON system is ideal for glue and resin removal work, surface preparation and floor levelling. Turning off the DCT (DCT OFF) lever will cause the main plate to rotate in the direction of the tools. In DCT OFF mode the planetarium is counter-rotating for general polishing, marble polishing, natural stone and concrete.




DCT ON: Only allows rotation of the tool holder satellites, this option makes HRC extremely effective and aggressive for the preparation, removal of glues and resins, for leveling the surface and for rapid exposure of the concrete aggregate.




DCT OFF: Allows rotation of the planetary in counter-rotating mode, ideal for sanding and polishing concrete, marble and natural stone floors.





DOUBLE CUT TECH

PLANETARY HRC SERIES



Discover the HRC 650 PLANETARY SYSTEM: Uncompromising Strength and Reliability.

The HRC 650 planetary system sets the standard for excellence in strength and reliability. Designed for long-term durability, it is the go-to solution for those seeking superior performance with zero worries.


Key Features:

- **Tempered steel gears:** Maximum strength and durability.
- **No belts prone to breakage:** Less maintenance, higher productivity.
- **Superior performance:** Ensures more stable, quieter, and efficient sanding.

Take your sanding experience to the next level with the new **HRC 650 PLANETARY SYSTEM**: reliability you can count on, performance that makes a difference.


HRC 650





WHY CHOOSE HRC

SETTING NEW
STANDARDS



EUROPEAN CERTIFIED

The HRC series complies with safety standards Art. EN 60204-1

TRANSMISSION WITH TEMPERED GEARS.

Planetarium in 100% tempered metal and without drive belt. The gear transmission system allows the machine to work continuously while maintaining high performance. No time wasted and pauses on the site construction due to broken belts. Belt drive planet gauges do not guarantee the same performance compared to planetary gearboxes, they are also subject to breakage during work and require long repair times. Warning: in many grinders the main dish and the satellites do not work together: if you lock a satellite the main dish keeps rotating, drastically reducing the performance of the machine.



SELECTOR TO LOCK THE INVERTER DOOR.

This device prevents opening the door before switching off the electrical panel.



SAFETY DEVICE DEDICATED TO MONITORING THE EMERGENCY CIRCUIT.

This device automatically switches off the machine in the event of a fault in the electrical system, preventing possible damage and repair costs. HG HYPER GRINDER uses the highest quality electrical components and complies with safety regulations.



ADJUSTABLE WEIGHTS.

180 ° overturning system for extra weight. The displaced weights increase the grinding pressure. The weights tilt back facilitating easy of use (optional).



EMERGENCY AND SAFETY BUTTON

The emergency button immediately stops the engine and all the "moving parts" (such as tools) avoiding any possible danger.



NEW DASHBOARD

HG Hyper Grinder introduces the new dashboard for the grinding machines. Cup holder and 2 USB sockets to make your job even more comfortable.



ADJUSTABLE HANDLE UP TO 90°

Handle in the rest position to reduce the clutter in the warehouse and in transport.



RAPID WATER CONNECTION

Convenient quick connection for connecting the water pipe directly. The tap allows you to adjust the water supply on the floor.



OPTIMIZED SUCTION SYSTEM.

Connection to the vacuum cleaner in order to work dry and without dust.



VARIABLE SPEED.

From 600 to 1300 rpm Many grinders on the market instead have a limited speed range.



46 LITER WATER TANK.

The water tank is imperative during wet grinding. Many grinding machines on the market do not have a tank or have a smaller one.



EFFECTIVE WEIGHT DISTRIBUTION.

The HRC grinders are built with the engine positioned on the centre of the planetary thus ensuring a perfect balance and maximum working pressure in all conditions and surfaces including Marble, Terrazzo and Concrete. Many grinders on the market, on the other hand, are not suitable for polishing and polishing marble floors.



WE GIVE IMPORTANCE TO STEEL.

HRC sanders are designed to be very robust and reliable over time:

- Frame in treated and painted steel.
- Planetarium sump is made of almond metal and galvanized for and protects from shocks.

Many grinders have a plastic casing that is easy to break, do not protect the tools from impact and do not allow to work flush against the wall.



2 YEARS WARRANTY

The GUARANTEE for HRC grinder with "hour counter" is extended up to 2 years or 600 hours. To receive the extended warranty you will need to follow the maintenance schedule at an authorized HG HYPER GRINDER workshop. The first maintenance must be performed within a year or 500 hours of work.

SETTING NEW
STANDARDS



HYPER
GRINDER

HRC
650



POWERFUL FRONT AND REAR LED
(OPTIONAL)







- 2 x 16A 1Ph 200V sockets • 1 16A 3Ph 5P 400V socket • 1 32A 3Ph 5P 400V socket • V0 self-extinguishing fiberglass cassette • IP 65 protection rating • 2 mt. of H07RN-F cable and CEE IP67 plug • Protected sockets with Interlocked Magnetothermic Differential • Emergency button always present • Grounding screw • Thermo-hardener handle for portable use • Brackets for wall mounting.

Particularly suitable for construction sites and uncomfortable environments.

The framework is equipped with the new LED system that helps you to always keep under control the line of your yard. It allows you to immediately identify where the fault is. The LED system also displays the arrival of the earth, allowing you to always work safely.

POWER ADAPTERS

with extension of 25 mt. 5G6 with 32A 5P 400V plug

TFG20101/SPRT Power adapters



- 2 x 16A 1Ph 200V sockets • 1 x 16A 3Ph 5P 400V sockets
- 1 x 32A 3Ph 5P 400V sockets • V0 self-extinguishing fiberglass case • IP 65 protection rating • 2 mt. of H07RN-F cable and CEE IP67 plug • Protected sockets with Interlocked Magnetothermic Differential • Emergency button always present • Grounding screw • Thermo-hardener handle for portable use • Brackets for wall mounting.

Particularly suitable for construction sites and uncomfortable environments.

The framework is equipped with the new LED system that helps you to always keep under control the line of your yard. It allows you to immediately identify where the fault is. The LED system also displays the arrival of the earth, allowing you to always work safely.

POWER ADAPTERS

Robust 200 from 25 mt. 5G10 3P + N + T with 63A Series HQ plug

TFG20101C Power adapters



EXTENSION FROM 25 MT.

5G6 with 32A 5P 400V plug

PR38073056 Extension



TESTER

network presence on a single phase + neutral + earth

TST-04	Three-phase plug 400V 5 poles 32A
TST-02	Three-phase plug 400V 5 poles 16A
TSM-01	Civil plug 200V 16A
TSM-02	Shuko plug 200V 16A

**EXTENSION**

Robust 200 from 25 mt. 5G6 3P + N + T
with 32A Series HQ plug

CM035701

Extension

**EXTENSION**

Robust 200 from 25 mt. 3G4 2P + T
with 16A Series HQ plug

CM036501

Extension

**EXTENSION**

Robust 200 from 25 mt. 5G6 3P + N + T
with 16A Series HQ plug

CM036101

Extension

**EXTENSION**

Robust 200 from 25 mt. 5G10 3P + N + T
with 63A Series HQ plug

CM035301

Extension

**MULTIPLE**

3 outputs 3P + N + T with 400V / 200V cable

VB1850

Multiple

**MULTIPLE**

with 3 outputs 1P + N + T with 200V cable

VB1552

Multiple

